

Magnetic attachment Flexible base



## Savings

Environmentally durable solution, reduced repair and maintenance costs.

## Anti-rodent

Environmentally durable solution, reduced repair and maintenance costs.

## Health

A safe, dry and draught free working environment for employees.

# Hygiene

Reduced dust, moisture and air pollution.

#### Installation

Quick, universal installation by unique patented magnetic fastening.

# Safety

Complies with the international health and safety regulations.





# RollMag Product specifications

# Specifications RollMag for Roller Shutter doors

Flexible, fi bre-reinforced material for inside and outside applications, UV and mildew resistant.

Temp. resistance

Coating

Tensile strength
Tear resistance
Built in depth/ width

Colour

Permanent magnet

Thickness

Material property Bonding capacity -20C up to +70C

Acrylate

2600/2400 (N/5cn) DIN 53354

250/250 (N) DIN 53386

>4mm/120mm

Standard color 7016, other RAL or black/ yellow and logo optional.

Universal installation

> 1,0 mm Anisotropic

Lifelong (without external infl uences)

## Available sizes

SAMTR 26

W=260mm L=1-9,2m


SAMTR 36


W=360mm L=1-9,2m

Standard color 7016, other RAL or black/ yellow and logo optional



High speed roller shutter






Can be supplied upto max 9200mm













IDD-Parts BV
Hanzeweg 19
3771 NG Barneveld
The Netherlands
T: +31 (0)342 490 990
E: info@iddparts.nl
www.iddparts.nl

IDD-Parts France Le Loup 13 rue du Morellon 38070 St Quentin Fallavier France T: +33 (0) 4 74 82 47 29 E: info@iddparts.fr www.iddparts.fr IDD-Parts Deutschland Hüntestrasse 72 26871 Papenburg/ Aschendorf Germany T: +49 (0)4962 9969 720 E: info@iddparts.de www.iddparts.de